

30-2500 KVA 10 KV Whole Sealing Oil-immersed Distribution Transformer

1. MODEL

VOITAGE GRADE: 10 KV

RATED CAPACITY: 30-2500 KVA

ON-LOAD TAP CHANGING/ PAN-SEAL/
THREE-PHASE



1. Product features

- (1) Energy-saving: The no-load loss, load loss, and operation cost are all lower.
- (2) Long service life: The transformer oil tank adopts a fully sealed structure. The oil tank and the tank edge can be connected by bolts. The transformer oil does not come into contact with the air, which prolongs the service life.
- (3) High operation reliability: The relevant parts and components related to the sealing of the oil tank have been improved, which increases the reliability. The process level is improved to ensure the reliability of the sealing.
- (4) Small floor space: The transformer oil tank uses corrugated plate radiators. When the oil temperature changes, the thermal expansion and contraction of the corrugated plates can replace the function of the oil conservator. The corrugated plate oil tank is beautiful in appearance and has a small floor space.

2. Main performance parameters

型 号 Type	额定容量 (KVA)	电压组合			联结 组标号	空载 电流 %	空载 损耗 KW	负载 损耗 (75°C) KW	短路 阻抗%
		高压(KV)	高压分 接范围	低压 (KV)					
S11-M-30	30	6 6.3 10 10.5 11	±5% 或 ±2× 2.5%	0.4	Yyno 或 Dyn11	2.1	100	630/600	4.0
S11-M-50	50					2.0	130	910/870	4.0
S11-M-63	63					1.9	150	1090/1040	4.0
S11-M-80	80					1.8	180	1310/1250	4.0
S11-M-100	100					1.6	200	1580/1500	4.0
S11-M-125	125					1.5	240	1890/1800	4.0
S11-M-160	160					1.4	280	2310/2200	4.0
S11-M-200	200					1.3	340	2730/2600	4.0
S11-M-250	250					1.2	400	3200/3050	4.0
S11-M-315	315					1.0	480	3830/3650	4.0
S11-M-400	400					1.0	570	4520/4300	4.0
S11-M-500	500					1.0	680	5410/5150	4.0
S11-M-630	630					0.9	810	6200	4.5
S11-M-800	800					0.8	980	7500	4.5
S11-M-1000	1000					0.7	1150	10300	4.5
S11-M-1250	1250					0.6	1360	12000	4.5
S11-M-1600	1600					0.6	1640	14500	4.5
S11-M-2000	2000					0.4	2100	17100	4.5
S11-M-2500	2500					0.32	2500	21000	4.5

Advanced Production Equipment

GNEE Steel Group owns a full set of shearing, packaging, vacuum casting, vacuum impregnation, and testing stations that represent the high level of the industry. These top-notch production and testing equipment guarantee the creation of first-class products. The company continuously improves its design methods, achieving the most advanced computer-aided design to meticulously craft perfect products.



Production Environment

The workshop of GNEE Steel Group has strict process management and a closed management system. Regular purification and dust removal tests are conducted to meet the necessary requirements for producing high and low voltage transmission products. It has also passed ISO9001 quality certification and third-party inspection certification for international bidding.



Autonomous Raw Material Supply

The iron cores and electromagnetic wires used in our company's products are all produced independently, which allows better control over the quality and delivery time of raw materials while reducing product costs.



Raw Material Production Environment



INTIMATE COMMUNICATION

Pre-sale, during-sale, and after-sale, we are with you every step of the way.

As long as you get in touch with us, we will communicate with you sincerely. Pre-sale, we will provide you with relevant product information; if you have special requirements, we can develop according to your needs and propose solutions under mutual recognition; during-sale, we will keep in touch with you throughout the process and inform you of the production progress, strictly following all the requirements in the contract; after-sale, our comprehensive "three guarantees" service system will ensure that you use our products with comfort, confidence, and satisfaction.

Inspection, Training, Guidance - All Free Of Charge.

As long as you are interested in our products and get in touch with us, we will take the initiative to contact you and arrange free inspections and factory experiences. We can also dispatch technical personnel to provide you with a free customized overall solution. Before the implementation of the solution, we will offer free training for your technical staff to inform them of the relevant knowledge about installation, commissioning, and maintenance of the product. During the equipment installation process, we will also provide you with free installation guidance. As long as it is your requirement, it is our mission; we will provide you with perfect services throughout the entire process.

Power Supply System Solutions Equipment Provider

Real Estate Development

In real estate development, container substations are widely used. In addition to short construction periods, low investment, small land occupation, and a new and beautiful appearance, the greatest advantage of this transformer is that it is installed in a moisture-proof, anti-corrosion, dust-proof, fire-proof, theft-proof, heat-insulating, fully enclosed, and mobile steel structure box. It integrates electromechanical equipment and runs fully enclosed, ensuring safety and long-term usability.



Industrial Enterprises

The fully sealed oil-immersed power transformer has the advantages of low loss, low noise, and high efficiency, which can achieve good energy-saving effects and reduce pollution. Compared with ordinary oil-immersed transformers, fully sealed transformers eliminate the need for an oil reservoir, and the changes in oil volume are automatically compensated by the elasticity of the corrugated oil tank's corrugated plates. The transformer is isolated from the air, preventing and slowing down the aging of oil and insulation, enhancing operational reliability, and requiring no maintenance during normal operation. Epoxy resin cast dry-type transformers can be used as updated replacement products for oil-immersed distribution transformers and are the best-performing products among various two-type transformers. They are particularly suitable for urban grids, high-rise buildings, business centers, theaters, hospitals, hotels, tunnels, subways, underground stations, laboratories, stations, docks, airports, combined substations, and other important places.



Oil Fields and Mines

High-efficiency energy-saving adjustable capacity transformers are designed based on the working characteristics of oil field pumping units. When the pumping unit starts, the transformer's output voltage is the rated input voltage of the motor, ensuring that the pumping unit has sufficient starting torque. After the pumping unit starts and enters the normal state, the control system will detect the size of the effective power consumed by the motor through sensors and feed it back to the microcomputer intelligent control system. Through calculations, it automatically adjusts the output voltage and capacity of the transformer, then detects, records, and compares the effective power consumed by the motor on the pumping unit, eventually finding the operating point where the consumption of effective power is minimal, achieving the purpose of energy saving. In terms of structural design, strong anti-theft measures have been taken, effectively preventing the theft of high-efficiency energy-saving transformers. At the same time, during the

energy-saving operation of the pumping unit, according to the set anti-electricity theft time method, the output voltage fluctuates, making it impossible for home appliances to function even if the electricity is stolen back. Therefore, the transformer has high-performance anti-theft functions.

